

ATEX crushing plant

for the chemical industry

Mechanical engineering **Realizations** **Cabling** **Machines**

This crushing station is used **to break up the powder agglomerates** of a product in order to facilitate its discharge into a reactor.

Crushing consists of a mechanical operation of **driving a tool into the material** to be treated. The movement is carried out using 4 pneumatic cylinders with a total thrust of **24,000 N**. A counter-pressure and its associated piloting prevent jolts of movement.

The bell covering the drum during treatment has a double function: counterweight to hold the drum and suction hood to contain volatile dust.

A door system at the entrance and exit **isolates the hazardous area**.

The station houses a conveyor system (not included in the CEREST supply) allowing the barrel to be moved.

Particular care was taken during the design **to limit the areas of material retention and facilitate the cleaning of the installation.**

The whole machine is designed to meet the **requirements of machines in explosive atmospheres (ATEX 2/22).**

SPECIFICATIONS :

- **ATEX 2/22**
- **For standard 200L drums**
- **24,000 N thrust in pneumatic**







Reference : 3502

Project added the 20/01/21

CEREST
20 Rue des Frères Lumiere
68000 Colmar - FRANCE

EMAIL
cerest@cerest.com

PHONE
+33 (0)3.89.21.02.56

INTERNET
www.cerest.com